



(11) Publication number : **0 594 529 A1**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number : **93630045.8**

(51) Int. Cl.<sup>6</sup> : **A46B 11/00**

(22) Date of filing : **01.07.93**

(30) Priority : **21.10.92 US 964195**

(43) Date of publication of application :  
**27.04.94 Bulletin 94/17**

(84) Designated Contracting States :  
**AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT SE**


(71) Applicant : **Greenhouse, Albert M.**  
**355 Southend Avenue, Apt. 29J**  
**New York, New York 10280 (US)**

(72) Inventor : **Greenhouse, Albert M.**  
**355 Southend Avenue, Apt. 29J**  
**New York, New York 10280 (US)**

(74) Representative : **Weydert, Robert et al**  
**Dennemeyer & Associates Sàrl P.O. Box 1502**  
**L-1015 Luxembourg (LU)**

(54) **Toothbrush.**

(57) An elongated housing structure (10) is provided for accommodating a toothbrush head (44) at one of its ends, and for insertion of a tube (20) of toothpaste through the other of its ends. A rotating pin (31) is provided to roll the bottom end (20') of the toothpaste tube (20), thereby to dispense the toothpaste, and to move forwardly of the housing (10) as the tube (20) becomes smaller. The forward motion of the pin (31) is accommodated by an elongated slot (28) defined by the housing (10). The top of the toothpaste tube (20) is selectively movable into and out of position with respect to the bristles (46) of the toothbrush (42), by means of a knurled knob (24) and depending collar (26) or neck holder movable in a second slot (22) defined by the housing (10). The toothbrush head (44) is movably connected to the front of the housing (10), so that the bristles (46) can be moved between a paste-loading position and a brushing position.



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 594 529 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**11.09.1996 Bulletin 1996/37**

(51) Int. Cl.<sup>6</sup>: **A46B 11/00**

(21) Application number: **93630045.8**

(22) Date of filing: **01.07.1993**

(54) **Toothbrush**

Zahnbürste

Broche à dent

(84) Designated Contracting States:  
**AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT  
SE**

(30) Priority: **21.10.1992 US 964195**

(43) Date of publication of application:  
**27.04.1994 Bulletin 1994/17**

(73) Proprietor: **Greenhouse, Albert M.  
New York, New York 10280 (US)**

(72) Inventor: **Greenhouse, Albert M.  
New York, New York 10280 (US)**

(74) Representative: **Weydert, Robert et al  
Dennemeyer & Associates Sàrl  
P.O. Box 1502  
1015 Luxembourg (LU)**

(56) References cited:  
**GB-A- 906 416                      US-A- 3 816 007  
US-A- 4 695 177**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 0 594 529 B1**

## Description

This invention relates primarily to toothbrushes and more particularly to a toothbrush-toothpaste tube combination structure.

Of course, for many years persons have placed at the top of their hygiene requirement list the use of implements for brushing their teeth. In point of fact, based upon various surveys and overviews of personal habits, nothing has yet been devised to replace the hand toothbrush as the means most used for performing that hygienic function.

In terms of such widespread use of the hand-held toothbrush, many have attempted to practically automate its use by combining it structurally with a means for pumping toothpaste to the top of the bristles of the toothbrush, or moving toothpaste to a point where it can be deposited at the bottom of the bristles of the brush. US-A-2,562,937 is an example of a mechanism for dispensing the toothpaste at the bottom of the bristles, as is US-A-4,615,635 and US-A-5,028,158. US-A-3,816,007 is an example of a mechanism mentioned above, which uses a complex reciprocal pump, with a pump-valve dispenser construction for moving the toothpaste tube to the use position at the top of the bristles of the toothbrush.

Another example of a pump-valve dispenser construction is US-A-4,695,177 which discloses a combined toothbrush and toothpaste holding and feeding structure for use in applying paste from a stationary toothpaste container onto a user's toothbrush bristles, comprising an elongated housing having a first end, a second end, and defining at the first end an opening for loading the toothpaste container, into the housing, a separate toothpaste applicator having an outlet, a valve between the container and the applicator, means for advancing said applicator toward the second end, the means for advancing providing a first position for the applicator with the outlet thereof within said housing and a second position for the applicator with the outlet outside of the second end, a toothbrush with bristles and a stem having a plunger, insertable to the housing through the second end, and means for positioning the bristles below the outlet when the applicator is in the second position, all adapted and arranged to load the toothpaste container into said housing, to pump toothpaste from the toothpaste container into the applicator by the toothbrush plunger actuating the valve, when the applicator outlet is positioned above the bristles, to apply toothpaste from the applicator outlet to the bristles and to brush the user's teeth, while remaining during the functioning as a unitary, combined structure.

Furthermore, other U.S. patents detail constructions, which provide mechanisms and structures similar to those mentioned above, and/or provide other mechanisms and structures to automate the paste-applying and/or toothbrushing functions. For instance, US-A-3,549,268 uses a rotating, bottom-tube control handle for controlling toothpaste feed automatically.

As to all of the above, the structures presented and suggested are particularly complex, cumbersome and expensive with respect to the function performed, and particularly with respect to the consideration that children make up a large portion of the user population.

Accordingly, a primary object of the present invention is to provide a combination toothpaste housing, toothpaste feeding mechanism, and toothbrush, which is simple and yet efficient in the performance of such functions.

A further object of the present invention is to provide a structure which is inexpensive, comfortable and easy to use, and which satisfies the performance of toothbrushing, toothpaste housing and toothpaste feeding functions; and

a further and additional object of the present invention is to combine multiple toothbrushing functions in a structure which is simple and yet comfortable for the user.

To achieve this, there is provided in accordance with the invention a combined toothbrush and toothpaste holding and feeding structure for use in applying paste from a toothpaste tube, including a tube nozzle, an opening defined by said nozzle and a tube bottom, onto a user's toothbrush bristles, comprising an elongated housing having a first end, a second end, and defining at said first end an opening for loading said toothpaste tube into said housing with its nozzle being loaded initially before its bottom, means for advancing said tube toward said second end, means for squeezing said tube bottom, said means for advancing providing a first position for said tube with said nozzle within said housing and a second position for said tube with said nozzle opening outside of said second end, a toothbrush with bristles and a stem, insertable to said housing through said second end, and means for positioning said bristles below said nozzle opening when said nozzle opening is outside of said second end in said second position of said tube, all adapted and arranged to load said toothpaste tube into said housing, to squeeze toothpaste from said toothpaste tube, when said toothpaste tube nozzle opening is positioned above said bristles and to brush the user's teeth, while remaining during said functioning as a unitary, combined structure.

Advantageous embodiments of the combined toothbrush and toothpaste holding and feeding structure are defined in the dependent claims.

Other features and advantages of the present invention will become apparent by the following, more detailed description of the preferred, but nonetheless, illustrative, embodiment, with reference to the accompanying drawings, wherein:

Fig. 1 is a front, right side and top isometric view of the present invention, showing particularly the loading mechanism, structure and procedure for the toothpaste tube, the collar, the connecting structure for the collar, the structure for providing movement

to the brush bristles, and the squeezing mechanism;

Fig. 2 is a sectional view, taken along the line 2-2 of Fig. 1 and showing particularly the motive capability of the squeezing structure, and the connecting structure for the collar and the structure for providing the motion to the bristles;

Fig. 3 is an enlarged view of the connecting structure and the motion structure, with respect to the collar and the structure for moving the bristles;

Fig. 4 is a front sectional view taken along the line 4-4 of Fig. 3 and showing particularly the front view of the connecting and motion structure, as previously briefly described;

Fig. 5 is a partial, enlarged view of the toothpaste tube mouth and collar of the present invention, with attached knob or wheel;

Fig. 6 is a front sectional view, taken along the line 6-6 of Fig. 5;

Fig. 7 is a top sectional view, taken along the line 7-7 of Fig. 2, and showing particularly the relationship of the mouth of the toothpaste tube with the second opening; and

Fig. 8 is a view, similar to that of Fig. 7, but showing the mechanism for thrusting the mouth of the toothpaste tube through the second opening.

Referring to the drawings, and particularly Fig. 1 thereof, a structure according to the preferred embodiment of the present invention is shown, along with use and assembly representations.

The preferred embodiment structure includes a housing, generally designated 10, having a top wall 12, a front wall 14, a right side wall 16 and a back wall 18. The back wall 18 is structured to include a door 18', which opens to admit toothpaste tube 20, (shown in ghost lines) in direction 19, at the rear of housing 10. Thumb indentation 21 is defined by top wall 12 in order to facilitate the opening of door 18'.

Top wall 12 defines an elongated slot 22, for providing the track for knob or wheel 24, which is connected rigidly to collar 26 (also see Figs. 2 and 5). Likewise, side wall 16 defines elongated slot 28 for tracking a squeezing mechanism and structure for toothpaste tube 20. More specifically, squeezing structure 30 is a knob 33 with extending wing surfaces 35, from which depends an elongated squeezing pin 31, defining elongated squeezing slot 32 for gripping the bottom end 20' of toothpaste tube 20.

Front end 14 of housing 10 defines a front opening 34, which is covered by front doors 36. Lower front opening 38, defined by front end 14, is to accommodate stem 40 of the toothbrush generally designated 42. Toothbrush 42 includes head 44, bristles 46 extending upwardly from head 44, stem 40, as previously described, and toothbrush base 48. Base 48, defines on its upwardly facing surface a plurality of ridges 50, essentially functioning as a gear surface (part of a rack and pinion type of structure).

Gear surface 50 is intended for mating with gear wheel 52, which in turn is intended to mate with gear surface 54 shown in ghost lines near the rear of the housing in Fig. 1, as defined by front toothpaste tube support 56 (also see Fig. 4). Gear wheel 52 (the pinion) is intended to fit upon axis 51 (see Figs. 2 and 3), between gear racks 54, 50, so that the forward motion in direction 27 (Fig. 5) of collar 26 causes the motion of toothbrush 42 rearwardly (with respect to the housing 10). Structurally, toothpaste tube support 56 has protruding from its forward end (see Figs. 2 and 3) a connecting clip 60 for attachment through opening 61 defined at the lower end of collar 26 (see Fig. 6).

More specifically, doors 36 (Figs 1, 7 and 8) are provided at the front end of housing 10 and thickly shaped in a manner not to interfere during operation with the threads 20" typically found at the open front end extension nozzle or top end of a toothpaste tube. Thus, the rearwardly extending part of doors 36 (best shown in Fig. 2) performs as a camming surface to push doors 36 open, without interference with threads 20".

Various alternative embodiments are contemplated for this invention. For instance, rather than the separate squeezing mechanism and structure previously described and the collar mechanism for moving the toothpaste tube in and out of the front of the housing, a combined mechanism and structure wherein a pair of gears or a single cylindrical gear depends onto tube 20 from a knurled knob travelling in slot 22, provides the squeezing and moving function all with a single mechanism, and without the use of winged knob 33. In other words, the weight and structure of the depending cylinder or gears of the alternative embodiment pushes tube 20 downwardly against a supporting platform (not shown).

Likewise, a tube squeezer is provided rearwardly of housing 10 for twisting toothpaste tube 20 from its bottom in order to feed the toothpaste.

Similarly, head 44 of toothbrush 42 is enlarged so that the toothbrush is placed into position below the front opening of toothpaste tube 20 for loading up bristles 46 with toothpaste and then manually pulled in direction 27 prior to the brushing operation. The enlarged head of this alternative embodiment is sufficient to accommodate the thumb and forefinger of the user, without the necessity for touching bristles 46, for hygienic reasons. Also in this regard, stem 40 of toothbrush 42 defines a protrusion to mate in two different positions with indentations defined by housing 10 in the area now occupied by lower rack or gear 50 and base 48. In other words, rack 50 and the entire double rack and pinion structure would not then be necessary in view of the manual operation of the alternative embodiment, to be coordinated by the user with the operation of knurled knob 24.

The immediately foregoing description of an alternative embodiment, for manual in-out motion of toothbrush 42 is usable with or without a further alternative relating to bifurcated stem 40, whereby the bristles 46

are manually turned upwardly for paste-loading and downwardly for brushing in order to avoid the interference or obstruction by housing 10, during the brushing process, with the mouth of the user. Specifically, the bifurcated stem involves the tightfitting mating of a forward part of stem 40, with a rearward part of stem 40, lockable in two positions, upwardly and downwardly, by the user, with a single protrusion and a pair of indentations (or vice-versa). This alternative serves the function of cutting down the length of stem 40, whose long length [about (five centimeters) two inches] is recommended for the preferred embodiment in order to avoid interference or obstruction by housing 10 with the user's mouth.

In all embodiments, a gripping surface 70 is defined by housing 10 on one or more of the side surfaces, in order to accommodate the user's grip during any of the manual operations indicated, and/or during the brushing operation. For instance, bottom wall 15 accommodates four fingers and top wall 12 defines a gripping surface to accommodate the thumb; or any other variation of gripping surfaces is provided.

Lastly, in order to provide a description of more of the alternatives indicated by the present invention, but all within the claims hereof, a cap (not shown) is provided for the mouth or front opening of toothpaste tube 20. For further hygienic protection, such cap (usually being provided by the toothpaste manufacturer) is designed with a flip-top cap or a threaded cap, or an extended nozzle opening.

In order to provide a more detailed and even clearer description of the present invention, a series of use and assembly steps are now provided. In typical fashion, a right-handed user grips housing 10, with his thumb on top wall 12 and with the four fingers of his left hand on lower wall 15. The right hand is then used to thrust collar 26 in direction 25 (Fig. 1) through slot 22, and to twist collar 26 (and attached knurled knob 24) ninety degrees. Tube 20 is then grasped by the same right hand so that its threaded neck 20" is placed through the upper large opening 23 of collar 26. Rack 54, 56, with forward protrusion 60 is placed through opening 61 defined by collar 26, so that it moves with the collar toward the front of housing 10. Knurled knob 24, by manipulation of the user's thumb, carries tube 20, lodged in collar 26 forwardly of housing 10. When tube 20 is wholly within housing 10, knob 33 is manipulated by the user's right hand to grasp bottom end 20' of tube 20, thus to enable the rolling, counterclockwise, squeezing motion for wings 35.

The user's own brush and stem structure (shown in ghost lines below Fig. 1) is thrust into opening 38 at the front of housing 10, so that rack 48, 50 meshes below pinion 52. As shown most clearly in Fig. 2, this thrusting, by the use of mechanical stops and the like (not shown), leaves approximately a five centimeter (two inch) stem 40 protruding to hold the bristles 46 facing upwardly. When ready for brushing, user's thumb 72 rolls knob 24 forwardly, in direction 27 to carry the toothpaste tube

forwardly, as shown by ghost lines in Fig. 2. Of course, simultaneously, the double rack and pinion mechanism carries stem 40 rearwardly, so that bristles 46 move to a position shown by ghost lines in Fig. 2, just below the opening defined by threaded nozzle or neck 20" of tube 20. If necessary, the user's right hand is then used to gently squeeze the bottom of tube 20, by rotating wings 35 in a counter-clockwise direction 39 with the user's right hand (see Fig. 2--ghost lines).

Following the flow of toothpaste 41 (Fig. 2) onto bristles 46, knob 24 is moved rearwardly of housing 10, in a direction opposite to the direction of arrow 27, in order to move the toothpaste tube back into housing 10, and simultaneously, bristles 46 and stem 40 forwardly of housing 10. This provides a full extension of bristles 46 away from the front of the housing in order to perform the brushing operation.

### Claims

1. A combined toothbrush and toothpaste holding and feeding structure for use in applying paste from a toothpaste tube (20), including a tube nozzle (20"), an opening defined by said nozzle (20") and a tube bottom (20'), onto a user's toothbrush bristles (46), comprising an elongated housing (10) having a first end, a second end, and defining at said first end an opening for loading said toothpaste tube (20) into said housing (10) with its nozzle (20") being loaded initially before its bottom (20'), means (24, 26) for advancing said tube (20) toward said second end, means (30) for squeezing said tube bottom (20'), said means (24, 26) for advancing providing a first position for said tube (20) with said nozzle (20") within said housing (10) and a second position for said tube (20) with said nozzle opening outside of said second end, a toothbrush (42) with bristles (46) and a stem (40), insertable to said housing (10) through said second end, and means (50, 52, 54, 56, 60, 61) for positioning said bristles (46) below said nozzle opening when said nozzle opening is outside of said second end in said second position of said tube (20), all adapted and arranged to load said toothpaste tube (20) into said housing (10), to squeeze toothpaste from said toothpaste tube (20), when said toothpaste tube nozzle opening is positioned above said bristles (46) and to brush the user's teeth, while remaining during said functioning as a unitary, combined structure.
2. The structure according to claim 1, wherein said means for advancing includes a collar (26) defining main and secondary openings (23, 61) therein, a knurled knob (24) attached to said collar (26) and said housing includes a top wall (12) defining an elongated slot (22) therein, said collar (26) being insertable to said slot (22) and rotatable therein with said knob (24), whereby said tube nozzle (20") is movable into said main opening (23).

3. The structure according to claim 2, wherein said means for squeezing includes a knob (33), an elongated squeezing pin (31) extending from said knob (33) in a direction perpendicular to said slot (22), said pin defining a squeezing slot (32) for gripping the bottom (20') of said tube (20) and said housing (10) having a side wall (16) which defines an elongated slot (28) extending generally from said first end to said second end, with said pin (31) movable toward said second end in said side wall slot as said toothpaste tube (20) is depleted. 5 10
4. The structure according to claim 2, wherein said toothbrush (42) also includes a base portion (48) at the opposite end of said stem (40) from said bristles (46), said means for advancing further includes a toothpaste tube support (56), extending forwardly of which is a means (60) for connecting said support (56) to said collar (26), and a pinion (52), which rotates between said base portion (48) and said support (56) to provide a double rack and pinion mechanism connecting the motion of said collar (26) and said stem (40), said base portion (48) and said support (56) each defining gear teeth surfaces (50, 54). 15 20 25
5. The structure according to claim 1, wherein said means for advancing includes a knurled knob (24), a top wall (12) for said housing (10) defining an elongated slot (22) in which said knob (24) moves, a bottom structure depending from said knob (24) for moving with said tube (20) from said first end to said second end, said means (30) for squeezing includes a squeezing structure connected to said tube bottom (20'). 30 35
6. The structure according to claim 1, wherein said means for positioning includes an enlarged toothbrush head (44) for providing a manual gripping surface. 40
7. The structure according to claim 1, wherein a door (18') is provided to cover said first end opening.
8. The structure according to claim 1, wherein a door (36) is provided at said second end between said first position and said second position. 45
9. The structure according to claim 1, wherein said housing (10) includes a plurality of side walls, a multiplicity of which define an outside gripping surface (70), in the form of finger indentations and a thumb indentation (21). 50
10. The structure according to claim 1, wherein said housing (10) includes a plurality of side walls, one of which defines an outside gripping surface (70), in the form of finger indentations. 55

## Patentansprüche

1. Kombinierte Zahnbürste und Zahnpastavorrats- und abgabestruktur zum Auftragen von Pasta aus einer Zahnpastatube (20), mit einem Tubenhals (20"), einer durch den Hals (20") geformten Öffnung und einem Tubenboden (20'), auf die Zahnbürstenborsten (46) eines Benutzers, mit einem länglichen Gehäuse (10), das ein erstes und ein zweites Ende aufweist und an dem ersten Ende mit einer Öffnung versehen ist zum Einführen der Zahnpastatube (20) in das Gehäuse (10), wobei der Tubenhals (20) zuerst vor dem Tubenboden (20") eingeführt wird, Mittel (24, 26) zum nach vorne Schieben der Tube (20) zu dem zweiten Ende hin, Mittel (30) zum Zusammendrücken des Tubenbodens (20'), wobei die Mittel (24, 26) zum nach vorne Schieben eine erste Stellung für die Tube (20) mit dem Tubenhals (20") innerhalb des Gehäuses (10) und eine zweite Stellung für die Tube (20) mit der Halsöffnung außerhalb des zweiten Endes bestimmen, einer Zahnbürste (42) mit Borsten (46) und einem Schaft (40), welcher in das Gehäuse (10) durch das zweite Ende einföhrbar ist und Mittel (50, 52, 54, 56, 60, 61) zum Einstellen der Borsten (46) unterhalb der Halsöffnung, wenn die Halsöffnung sich außerhalb des zweiten Endes in der zweiten Stellung der Tube (20) befindet, insgesamt ausgelegt und angeordnet zum Einführen der Zahnpastatube (20) in das Gehäuse (10), zum Herausdrücken von Zahnpasta aus der Zahnpastatube (20), wenn die Halsöffnung der Zahnpastatube unterhalb den Borsten (46) eingestellt ist und zum Bürsten der Zähne des Benutzers, unter Verbleib während dem Funktionieren als eine einheitliche, kombinierte Struktur.
2. Struktur nach Anspruch 1, wobei die Mittel zum nach vorne Schieben eine Halsplatte (26) aufweisen mit einer Haupt- und einer sekundären Öffnung (23, 61), einen geriffelten Knopf (24), der mit der Halsplatte (26) verbunden ist und das Gehäuse eine obere Wand (12) aufweist mit einem darin vorgesehenen Längsschlitz (22), wobei die Halsplatte (26) in den Schlitz (22) einföhrbar und über den Knopf (24) darin drehbar ist, damit der Tubenhals (20") in die Hauptöffnung (23) einföhrbar ist.
3. Struktur nach Anspruch 2, wobei die Mittel zum Zusammendrücken einen Knopf (33) und einen länglichen Quetschstift (31) aufweisen, der von dem Knopf (33) wegragt in einer Richtung senkrecht zum Schlitz (22), wobei der Stift einen Quetschschlitz (32) hat zum Erfassen des Bodens (20') der Tube (20) und das Gehäuse (10) eine Seitenwand (16) hat, mit einem Längsschlitz (28), der sich im wesentlichen vom ersten Ende zu dem zweiten Ende erstreckt, wobei der Stift (31) zum Entleeren der Zahnpastatube (20) in Richtung zu

dem zweiten Ende hin in dem Seitenwandschlitz beweglich ist.

4. Struktur nach Anspruch 2, wobei die Zahnbürste (42) ebenfalls einen Basisteil (48) an dem gegenüberliegenden Ende des Schaftes (40) von den Borsten (46) aufweist, die Mittel zum nach vorne Schieben des weiteren eine Auflage (56) für die Zahnpastatube aufweisen, von dem sich ein Ansatz (60) nach vorne erstreckt zum Verbinden der Auflage (56) mit der Halsplatte (26) und ein Ritzel (52), das zwischen dem Basisteil (48) und der Auflage (56) dreht zum Schaffen einer doppelten Zahnstangen- und Ritzeinheit, welche die Bewegung der Halsplatte (26) und des Schaftes (40) miteinander verbindet, wobei das Basisteil (48) und die Auflage (56) jeweils Getriebezahnflächen (50, 54) aufweisen.
5. Struktur nach Anspruch 1, wobei die Mittel zum nach vorne Verschieben einen geriffelten Knopf (24) aufweisen, wobei eine obere Wand (12) des Gehäuses (10) einen Längsschlitz (22) aufweist, in welchem der Knopf (24) beweglich ist, sowie ein Bodengebinde aufweist, das vom Knopf (24) nach unten ragt zur Bewegung mit der Tube (20) vom ersten zum zweiten Ende hin, wobei die Mittel (30) zum Zusammendrücken eine Quetschvorrichtung aufweisen, die an den Tubenboden (20') angeschlossen ist.
6. Struktur nach Anspruch 1, wobei die Mittel zum Einstellen einen vergrößerten Zahnbürstenkopf (44) aufweisen zum Schaffen einer manuellen Greiffläche.
7. Struktur nach Anspruch 1, wobei eine Tür (18') vorgesehen ist zum Abdecken der Öffnung des ersten Endes.
8. Struktur nach Anspruch 1, wobei eine Tür (36) vorgesehen ist an dem zweiten Ende zwischen der ersten Stellung und der zweiten Stellung.
9. Struktur nach Anspruch 1, wobei das Gehäuse (10) mehrere Seitenwände aufweist, wobei eine Mehrzahl dieser Seitenwände eine äußere Greiffläche (70) bilden, in Form von Fingervertiefungen und einer Daumenvertiefung (21).
10. Struktur nach Anspruch 1, wobei das Gehäuse (10) mehrere Seitenwände aufweist, wobei eine der Seitenwände mit einer äußeren Greiffläche (70) in Form von Fingervertiefungen versehen ist.

#### Revendications

1. Ensemble de brosse à dents et structure de conservation et de distribution de dentifrice à employer

pour appliquer du dentifrice d'un tube de dentifrice (20), muni d'un col (20"), d'une ouverture définie par le col (20") et d'un fond de tube (20'), sur les poils (46) d'une brosse à dents d'un utilisateur, comportant un boîtier allongé (10) ayant une première extrémité, une seconde extrémité, et délimitant à ladite première extrémité une ouverture pour charger ledit tube de dentifrice (20) dans le boîtier (10) avec son col (20") étant chargé initialement avant son fond (20'), des moyens (24, 26) pour faire avancer ledit tube (20) vers ladite seconde extrémité, des moyens (30) pour comprimer ledit fond de tube (20'), les moyens pour faire avancer (24, 26) fournissant une première position pour ledit tube (20) avec ledit col (20") situé à l'intérieur du boîtier (10) et une seconde position pour ledit tube (20) avec l'ouverture du col située à l'extérieur de ladite seconde extrémité, une brosse à dents (42) ayant des poils (46) et une tige (40), pouvant être insérée dans le boîtier (10) à travers ladite seconde extrémité, et des moyens (50, 52, 54, 56, 60, 61) pour positionner les poils (46) en dessous de l'ouverture du col lorsque l'ouverture du col se trouve à l'extérieur de ladite seconde extrémité dans ladite seconde position du tube (20), tout adapté et arrangé pour charger ledit tube de dentifrice (20) dans le boîtier (10) pour expulser du dentifrice dudit tube de dentifrice (20) lorsque l'ouverture du col du tube de dentifrice est disposée au-dessus des poils (46) et pour broser les dents de l'utilisateur tout en restant pendant ce fonctionnement une structure unitaire combinée.

2. Ensemble selon la revendication 1, dans lequel les moyens pour faire avancer comportent un collier (26) définissant une ouverture principale et une ouverture secondaire (23, 61) formées dans le collier, un bouton moleté (24) attaché audit collier (26), et le boîtier comporte une paroi supérieure (12), pourvue d'une rainure allongée (22), ledit collier (26) étant insérable dans ladite rainure (22) et rotatif dans celle-ci à l'aide du bouton (24), de sorte que le col (20") du tube puisse être engagé dans ladite ouverture principale (23).

3. Ensemble selon la revendication 2, dans lequel les moyens pour comprimer comportent un bouton (33), une tige de compression allongée (31) s'étendant à partir du bouton (33) dans une direction perpendiculaire par rapport à ladite rainure (22), ladite tige étant munie d'une rainure de compression (32) pour saisir le fond (20') dudit tube (20) et le boîtier (10) ayant une paroi de côté (16) définissant une rainure allongée (28) s'étendant essentiellement à partir de ladite première extrémité vers ladite seconde extrémité, ladite tige (31) étant mobile vers ladite seconde extrémité dans ladite rainure de la paroi de côté lorsque le tube de dentifrice (20) est vidé.

4. Ensemble selon la revendication 2, dans lequel la brosse à dents (42) est aussi munie d'une partie de base (48) à l'extrémité opposée de ladite tige (40) par rapport aux poils (46), les moyens pour faire avancer comportant également un support (56) 5 pour le tube de dentifrice, un moyen (60) s'étendant vers l'avant de ce support (56) pour connecter ledit support (56) audit collier (26) et un pinion (52) qui tourne entre la partie de base (48) et ledit support (56) en vue de fournir un mécanisme à double cré- 10 mailière et pignon connectant le mouvement dudit collier (26) et de ladite tige (40), ladite partie de base (48) et ledit support (56) définissant chacun des surfaces (50, 54) à dents d'engrenage. 15
5. Ensemble selon la revendication 1, dans lequel lesdits moyens pour faire avancer comportent un bouton moleté (24), une paroi supérieure (12) pour le boîtier (10) définissant une rainure allongée (22) dans laquelle le bouton (24) est déplaçable, une 20 structure inférieure s'étendant vers le bas dudit bouton (24) pour mouvement avec ledit tube (20) de ladite première extrémité vers ladite seconde extrémité, lesdits moyens (30) pour comprimer comportant une structure de compression connec- 25 tée audit fond (20') du tube.
6. Ensemble selon la revendication 1, dans lequel les moyens pour positionner comportent une tête (44) de brosse à dents agrandie pour fournir une surface 30 d'appui manuelle.
7. Ensemble selon la revendication 1, dans lequel une porte (18') est prévue pour couvrir ladite ouverture de la première extrémité. 35
8. Ensemble selon la revendication 1, dans lequel une porte (36) est prévue à ladite seconde extrémité entre ladite première position et ladite seconde position. 40
9. Ensemble selon la revendication 1, dans lequel le boîtier (10) comporte plusieurs parois de côté, une multitude de ces parois de côtés définissant une surface de prise externe (70) en forme d'encoches 45 pour les doigts et d'une encoche pour le pouce (21).
10. Ensemble selon la revendication 1, dans lequel le boîtier (10) comporte une pluralité de parois de 50 côté, l'une de ces parois étant pourvue d'une surface de prise externe (70) en forme d'encoches pour les doigts.

55



